

with the same body

- When `!!` is applied to `input$xxx`, the value is inlined.
- When `!!` is applied to a `metaReactive` read operation, the corresponding code is inlined.

expandChain

- When !! is applied to `input$xxx`, the value is inlined.
- When !! is applied to a `metaReactive` read operation, **a new variable is introduced if one doesn't already exist.**

withMetaMode

- When !! is applied to `input$xxx`, the value is inlined.
- When !! is applied to a `metaReactive` read operation, the corresponding code is inlined.

expandChain

- When !! is applied to `input$xxx`, the value is inlined.
- When !! is applied to a `metaReactive` read operation, **a new variable is introduced if one doesn't already exist.**

Example Shinymeta app

depends on

```
downloads <- metaReactive2({
  req(input$packages)
  metaExpr(cranlogs::cran_downloads(!input$packages,
    from = Sys.Date() - 365, to = Sys.Date()))
})
```

depends on

```
downloads_rolling <- metaReactive({
  !!downloads() %>%
  mutate(count = zoo::rollapply(count, 7, mean, fill = "extend"))
})
```

```
output$plot <- metaRender(renderPlot, {
  ggplot(!downloads_rolling(), aes(date, count)) +
    geom_line() +
    ggtitle("Seven day rolling average")
})
```